

TALCO

Fire Systems

ULR Commercial Packaged Fire Pumps



Talco ULR packages are CAD designed and built in complete compliance with NFPA-20. All components are UL/FM listed and suction & discharge fittings and piping sections are powder coated for long service life.

ULR systems offer flow rates from 50 to 1500 GPM with system pressures as high as 160 PSI.

System options include: Test Headers, Flow Meter Loops, City By-Pass Loops, Jockey Pumps, Auto-Transfer Switches, and a wide variety of controller options.

These packages are frame mounted, pre-wired, piped, fitted, and pressure tested before they leave our shop. All an installing contractor has to do is connect the suction & discharge piping, and provide the system with power.

ULR Packages can be customized to fit nearly any site layout or design condition. For more information, CAD drawings, and system cut-sheets go to Talcofire.com.



TALCO

Fire Systems

DIESEL - ELECTRIC - INLINE - SPLIT CASE - CENTRIFUGAL - TURBINE - SUBMERSIBLE

ULR SYSTEM FEATURES:

- Fully NFPA 20/13R Compliant
- Packages come piped, fitted, wired, and pressure tested
- Powder coated piping sections, fittings, & frame
- Flow rates from 50 to 1500GPM
- Pressures up to 160PSI
- Available in 45 standard configurations
- CAD files available for pump room drawings

SYSTEM OPTIONS INCLUDE:

- Test Headers
- City By-Pass Loops
- Flow Meter Test Loops
- Jockey Pumps
- FDCs
- Auto-Transfer Switches
- Multiple Controller Options

We can modify any system to fit your specific needs. Call for quote or more information.

